



4U Case RW-432G



4U Case RW-432G

1. Space for ATX and Extended ATX mainboards
2. Bay for PS/2 and mini-redundant power supplies
3. 2 cages with 4× vertical 5¼" bays each
4. Cages with 3× horizontal 5¼" bays optional
5. 3× 120 mm chassis fans in hot-swap frames
6. Space for 1× 60 mm chassis fan
7. Supervisor board for fans
8. Rear panel for ATX mainboards (for passive backplanes optional)

www.rackmax.de



RW-432G

- Valuable rack case with aluminium front
- Low TCO due to nice price and easy installation and maintenance
- Supports all PS/2, Long PS/2, and mini-redundant power supplies
- 2 removable 5¼" drive bays with rubber bearings for low-vibration operation and longer lifetime
- Cages with horizontal 5¼" bays (total of 6) for CD/DVD library solutions available as an option
- Lockable aluminium front door
- Chassis fans are electronically controlled and supervised
- On/Off and reset switch
- LED indicators for HDD activity, PSU and fan failure
- PCI card retainers in two different lengths for additional safety

LOGISTIC DATA:

Item #	10602
Net dimension (W×H×D)	426.5×177×680 mm (1'4¾"×7"×2'2¾")
Gross dimension (W×H×D)	545×300×840 mm (1'9½"×11⅞"×2'9⅛")
Net weight / gross weight	16.0 kg / 19.0 kg (35 lb 4 oz / 41 lb 14 oz)
Minimum order quantity	1 piece
Customs tariff #	84733090
Country of origin	Taiwan (R.O.C.)

TECHNICAL DATA:

Form factor	19" × 4U
Quantity of 5¼" bays	8× open (vertical) Optionally replaceable with 6× horizontal 5¼" bays
Quantity of extension slots	7× AGP/PCI (14× PCI optional)
I/O shield	Standard ATX
Mainboards supported	Passive backplane (optional) Full-size ATX, Extended ATX (up to 12"×13")
Chassis fans	3× 120 mm hot-swappable built-in 1× 60 mm mounted on the rear panel available as an option

