



SP-600A2C • Item # 12311

Features



- Compatible with Intel ATX12V Ver. 2.2 & 1.3
- "Super Low Noise" and stable output voltages under any load condition
- 2x (two) built- in PCI Express graphics card connectors
- 6x (two) Serial ATA harddisk connectors for your SATA drivers
- Active Power Factor Correction with a high PF value of > 0,98
- Excellent thermal management based on 12 cm fan
- Low power consumption in stand- by mode
- Automatic fan speed adjustment controlled by thermal sensor
- Low- noise, environment- friendly
- Protection against inrush currents, over currents, and over temperatures
- Short- circuit, over voltage, and under voltage protection
- 24 months warranty

ELECTRIC PARAMETERS

Model	SP-600A2C(RoHs)						
AC input	100-240Vac or 230 vac						
DC output	+3.3V	+5V	+12V ₁	+12V ₂	-12V	+5V _{SB}	
Max. Amps	24A	30A	18A	18A	0,8A	2A*	*peak 3,5A
Max. Combined	160W		36A (432W)				
Max. Combined	580W						
Total Power	600 Watt						

CABLE TABLE:

Model/ Type	SP-600A2C	length
M/B 20+4	1	500 mm
ATX12V (4P)	1	550 mm - 600 mm
EPS12V (8P)	1	550 mm - 600 mm
Peripherals (4P)	6	(400+100+100)mm x2
FDD (4P)	2	150 mm x2
SATA (5P)	6	(450+100+100)mm x2
PCI-E (6P)	2	550 mm x2

LOGISTIC DATA:

EAR-Reg. No.	EAR888-62976468
Article No.	12311
EAN Barcode	4250078130048
WEEE-Reg. No.	DE88670488
Pieces/Pallet	252
Size PSU Gross	228*92*223 mm
Size PSU Net	150*86*140 mm
Weight PSU Brutto	2.56 kg
Weight PSU Netto	2.16 kg
Customs tariff No.	85044020
Origination	China