



SP-400P2C • Item#: 11481

Features



- Compatible with Intel ATX12V Ver. 2.2
- "Super Low Noise" and stable output voltages under any load condition
- 2x (two) built- in PCI Express graphics card connectors
- 2x (two) Serial ATA harddisk connectors for your SATA drivers
- Passive Power Factor Correction with a high PF value of > 0.8
- Excellent thermal management based on 12 cm fan
- Low power consumption in stand- by mode
- Automatic fan speed adjustment controlled by thermal sensor
- Low- noise, environment- friendly
- Protection against inrush currents, over currents, and over temperatures
- Short- circuit, over voltage, and under voltage protection

ELEKTRIC PARAMETERS							
Model	SP-400P2C						
AC input	200~ 240Vac 6.0A 50Hz Passive PFC						
DC otuput	+3,3V	+5V	+12V ₁	+12V ₂	-12V	+5V _{SB}	
Max. Amps	22A	22A	18A	18A	0,8A	2A	
Max. Combined	150W		312W		9,6W	10W	
Max. Combined	380W				20W		
Total Power	400 Watt						

CABEL LABEL:			
Model/ Type		SP-400P2C	length
M/B	20+4	1	430 mm
ATX12V	(4P)	1	430 mm
Peripherals	(4P)	6	380 + 150 + 150 mm
FDD	(4P)	2	380 + 150 mm
SATA	(5P)	2	360 + 150 mm
PCI-E	(6P)	2	360 + 150 mm

LOGISTIC DATA:	
Item #	11481
WEEE-Reg. Nr.	EAR888-62976468
Pieces/Carton	6
PSU	150x140x86 mm
Carton	225x95x230 mm
PSU	1.96 kg
Carton	2.34 kg
Total Carton	14.86 kg
Customs Nr.	85044030
Origination	China